## **SPECIFICATIONS**

Meridian 9.2 NVR	2 TB	4 TB	8 TB		12 TB	16 TB
Form Factor	Small and compact Form Factor with 8-port POE switch					
Processor	Intel® Core™ Skylake i3-6100 Intel® Core™ Skylake i5-6500					
Memory	8 GB DDR4					
OS Drive	2.5-in SSD 128GB for Operating System and VMS Software					
Operating System	Microsoft® Windows 10 IoT Enterprise 64 bit					
Storage Drives	2 TB 3.5" SATA	4 TB 3.5" SATA	8 TB 3.5" SATA		12 TB 3.5" SATA	16 TB 3.5" SATA
Networking	Dual NIC, 2x 10/100/1000 Mbps RJ-45					
Built-in POE	8x 10/100 RJ-45 ports					
Video Output	2x Standard HDMI, 1x Display Port (Only 2 are supported simultaneously)					
Audio	Via HDMI or 3.5 mm audio jack 1x Mic-in / 1x Headphone-out					
Power Supply	200 W; 100 to 240 VAC, 50/60 Hz, Single non-redundant power supply					
Power Consumption	80 W min, 200 W max, POE power 120 W					
Recording Throughput	80 Mbps		120 Mbps			
Monitoring	Up to 220 FPS at 1080p		Up to 280 FPS at 1080p			
USB Ports	2x USB 3.0, 1x eSata					
Alarm I/O	4x alarm-in; 4x alarm-out					
Dimensions (H x W x D)	43.9 mm × 220 mm × 244.3 mm (1.72 in × 8.66 in × 9.62 in)					
Max Weight	2.5 kg (5.5 lb)					
Operating Tempera- ture	0°C to 40°C (32°F to 104°F)					
Warranty	3 years					
Certifications	UL, CE, FCC, LVD					

USS POE Switch (Item Sold Separately)			
RAM	32 KB SSRAM		
ROM	64 KB Flash Memory		
ID Range	8 bits		
Supported PoE Ports	8x 10/100 RJ-45 ports		
Uplink Port	1x 10/100/1000 Mbps RJ-45		
PoE Power Control	Yes (configurable)		
PoE Level	IEEE 802.3at		
Maximum Power of PoE	160 W		
Dimensions (H $\times$ W $\times$ D)	Dimensions (H $\times$ W $\times$ D)		
Unit Weight	1.6 kg (3.5 lb)		
Operation Temperature	0°C to 50°C (32°F to 122°F)		
Operation Relative Humidity	10% to 90% non-condensing		
System Power Supply	AC 100 to 240 V, 180 W		

## **Ordering Information**

Model	Description		
USS-MR08-P0E-02TB			
USS-MR16-P0E-04TB	Meridian NVR with 2 TB/4 TB/8 TB/12 TB/16 TB internal storage, 128 GB SSD for VMS and OS		
USS-MR24-P0E-08TB	and 8-port built-in POE switch. Includes 8/16/24 video channels, four users, four mobile connections and one		
USS-MR24-P0E-12TB	SDK connection license. Include 3 years free SSA.		
USS-MR24-P0E-16TB	include 3 years free 33A.		
SW08PE	Managed Ethernet switch with eight POE ports and smart web management		

Specifications are subject to change without notice. For the most up-to-date specs, go to www.flir.com/meridian

For more information contact: Sales@TeledyneFLIR.com or to find your local support number, visit: flir.com/contactsupport

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited. For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com.@2021 Teledyne FLIR, LLC. All rights reserved.

Revised on 04/12/22 Meridian\_Datasheet\_LTR\_20-0013

